




振动电机/ Unbalance vibrator

CRVX15C-3800 1.86kW 38kN 3Phs 4Poles/ 38KN 3相 4极

中文 EN 202501-1

Dat. 01/2025

TM



尺寸 / dimensions (mm)

A	B	C	D	E	F	Ø G
598	336	304	155	255	37	22
H	M	N				
155	243	322				



Ex db IIB T4 Gb Ex tb IIIC Tx Db IP66 7)

最高表面温度: 120°C  
max. surface temp.: 120°C

环境温度: -25° 到 +55°C  
Ambient temp.: -25° to +55°C

机械参数 / mechanical data

同步转速 synchronous speed		工作力矩 1) working moment		激振力 2) centrifugal force	整机重量 weight	轴承规格 bearing	润滑周期 Lube schedule	电源线缆接口尺寸 wiring cable connection	防护等级 protection	噪音分贝 5) noise level
Hz	RPM	kgcm	in-lbs	kN	kg	SKF FAG NJ2312 C4	每运行2000小时 每个轴承加40克  every 2000 working hrs add 40g per bearing	3/4" NPT	IP66	dB(A)  73
50	1500	311.8	270.6	38	139					
60	1800	214	185.8	38	130					

电气参数 / electrical data

额定转速 nominal speed	额定功率 rated power	效率 efficiency	绕组电阻值 4) coil resist	耐热等级 thermal class	比值 启动/额定 ratio starting / rated		额定电流 rated current I <sub>N</sub>			
					电流 current	转矩 torque	Hz	V	A	
Hz	min <sup>-1</sup>	kW	Ω	H	I <sub>A</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub>	50	Δ	220-240	7.3
								Y	380-415	4.3
								Y	500-525	3.3
								Y	660-690	2.5
								Δ	254-277	6.7
								Y	440-480	3.7
50	1470	1.865	3.1	H	6	2.7	60	Δ	254-277	6.7
								Y	440-480	3.7
60	1764	1.960	3.1	H	6	2.7	60	Y	550-600	4.4

安装和维护 / assembly and maintenance

紧固件 fastening			润滑脂: Klüber STABURAGS NBU8 EP	出厂已加注	添加润滑脂 3)	润滑周期 6)	环境温度	电源线缆
螺栓规格 thread	等级 material	预紧力 moment	grease: Klüber STABURAGS NBU8 EP	greas filling	re-lubrication	lubrication intervals	Ambient temperature	cable
							100g	
4x M20 1" 14NF	8.8  Gr8	Nm  266	轴承温度80°C 以下时/Bearing temp. until 80°C		40g	2000 h	-25°/+55°C	参考操作手册 refer to Operators Manual
			轴承温度80°C -95°C时/Bearing temp.80°C - 95°C		10g	750 h		
			轴承温度超过/Bearing temp. Over 95°C	咨询技术人员 /ask technical office				
Revision: 01 202501								

- 1) 工作力矩 = 2x 静态力矩 /working moment= 2x static unbalanced weight
- 2) 同步转速最大振幅 / max. value at synchron. speed
- 3) 单个轴承/ per bearing
- 4) 环境温度20°C/ Ω@20°C
- 5) 1米距离/ at a distance of 1m
- 6) 第一次添加双倍的量/ first regreas. with double qty of grease
- 7) EX-气体和粉尘防爆认证/ explosion-proof design

